

Driver LC 38W 650–1050mA 42V bDW NFC SC EXC3
excite series



With strain-relief



Product description

- _ Can be integrated in Casambi systems (Casambi Ready)
- _ NEW: lumDATA (Luminaire data, Energy reporting and Diagnostics & Maintenance)
- _ Can be either used built-in or independent with clip-on strain-relief (see accessory)
- _ Forms automatically a wireless communication network with up to 250 nodes
- _ Dimming range 1 – 100 % (min. 5 mA)
- _ For luminaires of protection class I and protection class II
- _ Temperature protection as per EN 61347-2-13 C5e
- _ Adjustable output current between 650 – 1,050 mA via NFC
- _ Max. output power 38 W
- _ Up to 87 % efficiency
- _ Lowest power input on stand-by < 0.45 W
- _ Nominal lifetime up to 100,000 h
- _ 5 years guarantee (conditions at www.tridonic.com)

Housing properties

- _ Casing: polycarbonate, white
- _ Type of protection IP20

Interfaces

- _ basicDIM Wireless
- _ Near field communication (NFC)
- _ Terminal blocks: 45° push terminals

Functions

- _ Adjustable output current in 1-mA-steps (NFC)
- _ Enhanced constant light output function (eCLO)
- _ Protective features (overtemperature, short-circuit, overload, no-load)
- _ Suitable for emergency escape lighting systems acc. to EN 50172

Benefits

- _ Flexible configuration via companionSUITE (NFC)
- _ Application-oriented operating window for maximum compatibility
- _ Best energy savings due to low stand-by losses and high efficiency
- _ In-field programming possible after installation with NFC interface

Typical applications

- _ For downlight, spotlight and decorative applications

Website

<http://www.tridonic.com/28003716>



Spotlights



Downlights



Linear



Area



Floor | Wall



Free-standing



Street




Decorative



High bay

Driver LC 38W 650–1050mA 42V bDW NFC SC EXC3
excite series

The complete data sheet for this product is available in the Downloads section.



Ordering data

Type	Article number	Packaging, carton	Packaging, pallet	Weight per pc.
LC 38/650-1050/42 bDW NF SC EXC3	28003716	10 pc(s).	920 pc(s).	0.159 kg
LC 38/650-1050/42 bDW NF SC EXC3	28003716	10 pc(s).	920 pc(s).	0.159 kg

Technical data

Rated supply voltage	220 – 240 V
AC voltage range	198 – 264 V
DC voltage range	176 – 280 V
Mains frequency	0 / 50 / 60 Hz
Overvoltage protection	320 V AC, 48 h
Typ. rated current (at 230 V, 50 Hz, full load) ^{①②}	196 mA
Typ. current (220 V, 0 Hz, full load, 15 % dimming level) ^②	35.4 mA
Leakage current (at 230 V, 50 Hz, full load) ^{①②}	< 250 µA
Max. input power	44.3 W
Typ. efficiency (at 230 V, 50 Hz, full load) ^②	87 %
λ (at 230 V, 50 Hz, full load) ^①	0.97
λ (over full operating range)	0.57C – 0.97
Typ. power consumption on stand-by	< 0.45 W
In-rush current (peak / duration)	5.33 A / 42 µs
THD (at 230 V, 50 Hz, full load) ^①	< 10 %
Starting time (AC mode)	< 900 ms
Starting time (DC mode)	< 500 ms
Switchover time (AC/DC) ^③	< 800 ms
Turn off time (at 230 V, 50 Hz, full load)	< 50 ms
Output current tolerance ^{①④}	± 5 %
Max. output current peak (non-repetitive)	≤ output current + 20 %
Output LF current ripple (< 120 Hz)	± 5 %
Output P _{ST_LM} (at full load)	≤ 1
Output SVM (at full load)	≤ 0.4
Max. output voltage (U-OUT)	60 V
Dimming range	1 – 100 % (min. 5 mA)
Mains surge capability (between L - N) ^⑤	1 kV
Mains surge capability (between L/N - PE)	2 kV
Burst protection	1 kV
Burst / surge peaks output side against PE	< 3 kV
Ambient temperature t _a	-20 ... +50 °C
Max. casing temperature t _c	87 °C
Radio transceiver operating frequencies	2.4 – 2.483 GHz
Max. output power radio transceiver (E.R.I.P.) ^⑥	< + 20 dBm
Type of protection	IP20
Lifetime	up to 100,000 h
Guarantee	5 Year(s)
Dimensions L x W x H	97 x 43 x 30 mm

Approval marks**Standards**

EN 55015, EN 61000-3-2, EN 61000-3-3, EN 61000-4-4, EN 61000-4-5, EN 61347-1, EN 61347-2-13, EN 62384, EN 61547, according to EN 50172, according to EN 60598-2-22

Specific technical data

Type	Output current ^①	Min. output voltage	Max. output voltage	Max. output power	Typ. power consumption n (at 230 V, 50 Hz, full load)	Typ. current consumption n (at 230 V, 50 Hz, full load)
LC 38/650-1050/42 bDW NF SC EXC3	650 mA	7.5 V	42.0 V	27.3 W	32.3 W	154 mA
LC 38/650-1050/42 bDW NF SC EXC3	650 mA	7.5 V	42.0 V	27.3 W	32.3 W	154 mA
LC 38/650-1050/42 bDW NF SC EXC3	700 mA	7.5 V	42.0 V	29.4 W	34.9 W	166 mA
LC 38/650-1050/42 bDW NF SC EXC3	700 mA	7.5 V	42.0 V	29.4 W	34.9 W	166 mA
LC 38/650-1050/42 bDW NF SC EXC3	800 mA	7.5 V	42.0 V	33.6 W	39.3 W	185 mA
LC 38/650-1050/42 bDW NF SC EXC3	800 mA	7.5 V	42.0 V	33.6 W	39.3 W	185 mA
LC 38/650-1050/42 bDW NF SC EXC3	905 mA	7.5 V	42.0 V	38.0 W	44.2 W	207 mA
LC 38/650-1050/42 bDW NF SC EXC3	905 mA	7.5 V	42.0 V	38.0 W	44.2 W	207 mA
LC 38/650-1050/42 bDW NF SC EXC3	1,050 mA	7.5 V	36.2 V	38.0 W	43.6 W	196 mA
LC 38/650-1050/42 bDW NF SC EXC3	1,050 mA	7.5 V	36.2 V	38.0 W	43.6 W	196 mA

① Valid at 100 % dimming level.

② Depending on the selected output current.

③ Valid for immediate change of power supply type otherwise the starting time is valid.

④ Output current is mean value.

⑤ L-N acc. to EN 61000-4-5. 2 Ohm, 1.2/50 µs, 8/20 µs.

⑥ E.I.R.P.: Equivalent Isotropically Radiated Power.