



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

## Micro Plug Connector panel-mounted 3p Screw GRD M16 IP66/IP68/IP69

Code: **THB.381.N3E**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

## GENERAL INFORMATION

Type of installation	Plug and Socket connector
Product configuration	Panel nut mounting plug
	<i>*Fixing nut included in the kit</i>
Locking mechanism	Push Pull
Colour	Black (Plastic components) - Techno green (Rubber components)
Type of panel	Conductive panel
Panel nut thread	M16
Panel thickness (mm)	7.00
Connector shape	Straight

## ELECTRIC DATA

No. connected cables	1
Circuit wiring diagram	Power
Current rating (AC/DC)	10A
Voltage rating (AC/DC)	500V AC
Double insulated (Class II)	250V
Impulse withstand voltage	4kV
No. poles	3
Marking	L-N-E
Terminations	Hex socket screw
Terminations Thread/Tightening torque	M2 - 0.1 Nm

## CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm <sup>2</sup> )	0.25
Multi-stranded conductor cross-section without ferrule MAX (mm <sup>2</sup> )	1.00
Conductor stripping length (mm)	10.00
Cable sheath stripping length (mm)	20.00
Recommened types of cable	H05xxx/H07xxx
Tightening torque of panel nut	1.5 Nm

## ENVIRONMENT CONDITIONS

IP rating	IP66, IP68, IP69
	<i>*IP68 (30m/1h)</i>
Salt Mist	Salt mist test : EN60068-2-11:2000
Mating cycles	100 cycles
Ambient temperature MIN/MAX (According to EN61984/EN60998)	-40°C/+125°C
Operating temperature MAX	+60°C
Proof Tracking Index (PTI)	PTI 175

## MATERIALS

Connector	PA66 GF UL94 V0
Cable gland	PA66 GF UL94 V2
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

## PRODUCT COMPLIANCES

IEC Approvals	EN 61984:2009
---------------	---------------

## COMMERCIAL DATA


EAN	8057457095938
Packing method	Bulk packed ( OEM )
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	7.60
Overall dimensions of box (mm)	300 x 200 x 180
Corresponding code in KIT	THB.381.N3E.R
Custom tariff number	85369010
Country of origin	ITALY

## APPROVALS

Please login to access this data.

## TECHNICAL DOCUMENTATIONS

### Technical documentations:

File	Type	Size
 606002034_TH381 PANEL INSTALLATION.pdf	PDF	801.73 KB

## CAD FILES

Please login to access this data.

## MARKETING DOCUMENTS

Please login to access this data.

