



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

KIT Micro Junction Connector "H" 2p Screw L-N IP66/IP68

Code: **THB.395.H2E.R**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	Junction connector
Colour	Black (Plastic components) - Green (Rubber components)
Overall dimensions (mm)	105.0 x 40.0 x 16.4

ELECTRIC DATA

No. connected cables	4
Circuit wiring diagram	Signal
Current rating (AC/DC)	10A AC/DC
Voltage rating (AC/DC)	500V
No. poles	2
Marking	L-N
Terminations	Screw
Terminations Thread/Tightening torque	M2 - 0.2 Nm

CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.25
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	1.50
Solid conductor cross-section MIN (mm ²)	0.25
Solid conductor cross-section MAX (mm ²)	1.50
Conductor stripping length (mm)	8.00
Main cable sheath stripping length (mm)	20.00
Branch cable sheath stripping length (mm)	20.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	5.40
Cable diameter MAX (mm)	7.90
Tightening torque of cable gland-connector	1.0 Nm
Tightening torque of nut-cable gland	1.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68, IP66 <i>*IP68 (2m/24h)</i>
T marking	T 85°C
Proof Tracking Index (PTI)	PTI 175

MATERIALS

Exterior body	TPE
Connector	PA68 GF UL94 V0
Cable gland	PA66 UL94 V0
O Rings	TPE
Gaskets	TPE
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES



IEC Approvals	EN 60998-1:2004
---------------	-----------------

COMMERCIAL DATA

Packing method	Individually packed (KIT)
Type of packaging	Blister
Pieces/kit (pcs)	1
Pieces/box (pcs)	30
Overall dimensions of box (mm)	300 x 200 x 160
Corresponding code in Box	THB.395.H2E
Custom tariff number	85369010
Country of origin	ITALY


APPROVALS

REACH/RoHS Approvals:

File	Type	Size
 REACH.pdf	PDF	105.87 KB
 RoHS Compliance.pdf	PDF	84.57 KB



TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606002065_install sheet_TH395.pdf	PDF	2.21 MB

MARKETING DOCUMENTS

Marketing documentations:

File	Type	Size
 Techno_Guida_Installativa_ITA_20251107.pdf	PDF	6.65 MB
 Techno_Guida_Installativa_ENG_20251107.pdf	PDF	6.65 MB