



A+
energy class

94
lumens/watt


Tracklight LUX

LED Track Spot LUX 930 32W S 25D BK
93113175

Product information


Precise accent lighting designed for retail applications, art galleries and museums. The Lux range track spot has a unique patented design, self cleaning lens and sleek appearance making it an attractive proposition for any project. Over 50% energy saving compared to Ceramic Metal Halide thanks to the high efficacy up to 100lm/W. This CR90 option with 3-step MacAdam ellipses offers high quality lighting for high end applications. The wide range of accessories and interchangeable lens options makes this a flexible and highly attractive option.

TUNGSRAM 93113175
LED Track Spot LUX
930 32W S 25D BK

 This luminaire contains built-in LED lamps.

LED

The LED lamps cannot be changed in the luminaire

874/2012 

Product data

Product code	93113175
Description	LED Track Spot LUX 930 32W S 25D BK
DIALux description	TUNGSRAM - Tracklight LUX - 3000lm - 32W - 3000K - 90CRI - 93113175[SKU] - Track mount
Brand	TUNGSRAM
Product category	Trackspot LUX
Product family	Tracklights
Application areas	Hospitality, Museums, Retail
DUN Code	10064894571111
Light source	LED
Sensor	No sensor
Emergency option	No EM
Mounting type	Track mount
Weight [kg]	1,09
Body color	Black
Product dimensions (Length) x (Width) x (Height) [mm]	140 x 96 x 182
Operating temperature min [°C]	-20
Operating temperature max [°C]	40
Rated ambient temperature (tq) [°C]	25
Cooling	Passive
Certifications	CE
General warranty [year]	5

Performance data

System power [W]	32
Nominal luminous flux [lm]	3000
Rated efficacy [lm/W]	94
Rated life L70/B50 [h]	50000
IP front (optical)	20
IP back (electrical)	20
IP Rating	20
Energy efficiency class (EEC)	A+

Photometrical data

Photometric distribution	Spot
Nominal correlated colour temperature (CCT) [K]	3000
Colour rendering index (CRI) [Ra]	≥ 90
Nominal beam angle [°]	25
UGR value (4H8H)	19,3
Colour consistency in MacAdam steps SDCM	≤ 3
Photobiological risk	RG1


Electrical data

IEC protection class	Class I
Operating voltage [V]	220-240V
Rated frequency or frequency range [Hz]	50/60Hz
Lamp input current [mA]	145
Nominal lamp power factor	≥ 0.95
Controllability	Static

Logistic data

Box quantity	1
Shipment	Standard
Product status	Available
Accessory	93062906/93061745/13498/13499/13504/13508

Light distribution



Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Datasheet \(PDF\)](#)

[Installation guide - Static \(PDF\)](#)

[Installation guide - DALI \(PDF\)](#)

[Images \(HTTP\)](#)

[Doc documents - Static \(PDF\)](#)

[Doc documents - DALI \(PDF\)](#)

[Photometrics with lenses \(HTTP\)](#)

[Datasheet \(FR\) \(PDF\)](#)