



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Junction Connector "Y" 2p Screw D7-13.5 IP68

Code: THB.399.A8B



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Joint connector (re-usable/re-accessible)
Product configuration	Junction connector
Colour	Black (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	Ø 34.0 x 65.5 x 180

ELECTRIC DATA

No. connected cables	3
Circuit wiring diagram	Power
Current rating (AC/DC)	32A
Voltage rating (AC/DC)	450V AC
No. poles	2
Marking	L-N
Terminations	Screw
<i>*Terminal block with double connection, the piercing solution is ideal for PVC, Neoprene and FEP cables</i>	
Terminations Thread/Tightening torque	M3 - 0.8 Nm

CONNECTION DATA

**To reduce the cable diameter from 6 to 7 mm, the reducer code 6000087LF must be used, sold separately.*

Multi-stranded conductor cross-section without ferrule MIN (mm ²)	0.50
Multi-stranded conductor cross-section without ferrule MAX (mm ²)	4.00
Solid conductor cross-section MIN (mm ²)	0.50
Solid conductor cross-section MAX (mm ²)	4.00
Conductor stripping length (mm)	8.00
Main cable sheath stripping length (mm)	50.00
Branch cable sheath stripping length (mm)	30.00
Reccomended types of cable	H05xxx/H07xxx
Cable diameter MIN (mm)	7.00
Cable diameter MAX (mm)	13.50
Tightening torque of cable gland-connector	2.5 Nm
Tightening torque of nut-cable gland	2.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP68
<i>*IP68 (20m/1h)</i>	
IK rating	IK07
Salt Mist	Salt mist test : EN60068-2-11:2000
T marking	T 125°C
Proof Tracking Index (PTI)	PTI 250

MATERIALS

Exterior body	PA66 GF UL94 V0
Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	Silicone
Gaskets	TPE
Material property	Halogen Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals	EN 60998-1:2004
---------------	-----------------

COMMERCIAL DATA

EAN	8057457094634
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	100
Weight per Piece (gr)	105.10
Overall dimensions of box (mm)	600 x 270 x 400
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606001500_IST_TH399.pdf	PDF	863.40 KB

DRAWINGS

Drawings:

File	Type	Size
 THB_399_AXA.pdf	PDF	155.62 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.
