



The image has the only illustrative purpose and it is purely indicative, it may not fully reflect the product configuration.

Mini Plug Connector panel-mounted 5p Screw M20 IP66/IP68

Code: **THB.389.L5E**



Potential improvements of the product and modifications of the technical data contained in this document can be made without notice.

GENERAL INFORMATION

Type of installation	Plug and Socket connector
Product configuration	Panel nut mounting plug
	<i>*Fixing nut included in the kit</i>
Locking mechanism	Push Pull
Colour	Black/Brown (Plastic components) - Techno green (Rubber components)
Overall dimensions (mm)	Ø 23.0 x 20.03
Overall dimensions when mated together (mm)	Ø 23.0 x 80.0
Panel nut thread	M20
Panel thickness (mm)	3.00
Connector shape	Straight

ELECTRIC DATA

No. connected cables	1
Circuit wiring diagram	Power/Signal
Current rating (AC/DC)	17.5A AC/DC
Voltage rating (AC/DC)	500V AC
Impulse withstand voltage	4kV
No. poles	5
Marking	1-2-3/L-N-E
Terminations	Screw
Terminations Thread/Tightening torque	M2 - 0.2 Nm

CONNECTION DATA

Multi-stranded conductor cross-section without ferrule MIN (mm²)	0.25
Multi-stranded conductor cross-section without ferrule MAX (mm²)	1.50
Solid conductor cross-section MIN (mm²)	0.25
Solid conductor cross-section MAX (mm²)	1.50
Conductor stripping length (mm)	6.00
Cable sheath stripping length (mm)	25.00
Reccomended types of cable	H05xxx/H07xxx
Tightening torque of panel nut	1.5 Nm

ENVIRONMENT CONDITIONS

IP rating	IP66, IP68
	<i>*IP68 (5m/1h)</i>
Salt Mist	Salt mist test : EN60068-2-11:2000
Ambient temperature MIN/MAX (According to EN61984/EN60998/EN62444)	-40°C/+100°C
Operating temperature MAX	+70°C
Proof Tracking Index (PTI)	PTI 175

MATERIALS

Connector	PA66 GF UL94 V0
Cable gland	PA66 UL94 V2
O Rings	TPE
Gaskets	TPE
Impulse withstand category	II
Pollution degree	2
Material property	Halogen Free - Silicone Free
Contacts	Brass
Contact screws	Steel

PRODUCT COMPLIANCES

IEC Approvals	EN 61984:2009
---------------	---------------

COMMERCIAL DATA

EAN	8057457098045
Packing method	Bulk packed (OEM)
Type of packaging	Box
Pieces/box (pcs)	200
Weight per Piece (gr)	17.96
Corresponding code in KIT	THB.389.L5E.R
Custom tariff number	85369010
Country of origin	ITALY

APPROVALS

Please login to access this data.

TECHNICAL DOCUMENTATIONS

Technical documentations:

File	Type	Size
 606002037_Istruzioni_TH389_pannello_web.pdf	PDF	1.45 MB

DRAWINGS

Drawings:

File	Type	Size
 THB_389_L5E.pdf	PDF	230.55 KB

CAD FILES

Please login to access this data.

MARKETING DOCUMENTS

Please login to access this data.