





PRODUCT CODE / CODICE PRODOTTO

9500-2/W2-ST13-E

DESCRIPTION / DESCRIZIONE

ELECTRIFIED 4-CONDUCTOR RECESSED TRACK TRIMLESS

BINARIO ELETTRIFICATO A 4 CONDUTTORI DA INCASSO TRIMLESS



TECHNICAL DATA / DATI TECNICI

Rated current and voltage: 15A/60V dc

Rated current and voltage:

FEATURES / CARATTERISTICHE

Materials: External extruded body in aluminium; Insulated extruded body in PVC; Copper conductors

Materiali: Estruso esterno in alluminio; Estruso isolante in PVC; Conduttori in rame

Length: 2000 mm

Length:

Available colours: White RAL 9016

Colori disponibili: Bianco RAL 9016

Fastening: Trimless

Fissaggio: Trimless

Weight: 2321,3 g

Peso:

Max load: 25 kg/m - Panel weight/m (see assembly instructions)

Carico: 25 Kg/m - Peso pannelli/m (vedi istruzioni di montaggio)

Information / Informazioni



SELV

Certifications / Certificazioni



Class 2
48Vdc-2A
not polarized use



ACCESSORIES / ACCESSORI



9504/ST1-...

Notes / Note

Track for both polarized and non polarized versions
For a correct installation use with S-9500/D1-ST13, to be bought separately.

*Binari per utilizzo in versione sia polarizzata che non polarizzata
Per una corretta installazione utilizzare con art S-9500/D1-ST13, da acquistare separatamente.*