

A.A.G. STUCCHI s.r.l. u.s
Via IV Novembre 30/32
23854 Olginate (LC)
www.aagstucchi.it
info@aagstucchi.it





SENZAFINE HE MAIN VOLTAGE LENS / *SENZAFINE HE MAIN VOLTAGE LENS*

PRODUCT CODE / *CODICE PRODOTTO*

M141500/W8-C-2-MV

DESCRIPTION / *DESCRIZIONE*


230V linear light module. For 9000/9000A ONETRACK™ range tracks. PMMA Lens 37°. Polycarbonate cover. L(mm): 1628.


230V linear light module. For 9000/9000A ONETRACK™ range tracks. PMMA Lens 37°. Polycarbonate cover. L(mm): 1628.

TECHNICAL DATA / *DATI TECNICI*

Application	ON TRACK
Real Flux(lm)	3287.96
Nominal Flux(lm)	3887.3
Real Power(W)	33.9
Efficiency(lm / W)	97.0
LED source	LED
Colour Temperature(K)	2700
CRI	90
MacAdam	≤ 3
Beam Angle	37,4°x37,0°
UGR	<16
Lifetime(Khr)	>60Khr L90B5
Driver	DALI 2
VF	~ 49
I LED(mA)	600mA
L(mm)	1628
Weight(g)	600
Materials	Aluminium body + PMMA lenses + polycarbonate covers
Colour	Bianco
Mounting	Mechanical
Packaging	Tube

	X=4H Y=8H	S=0.25H
	Reflection factors:	70/50/20
	UGR transversal:	14
	UGR axial:	13.8





Room (m): 4x4x3h H luminaire (m): 2,5 Ref. surface: floor

Certifications / *Certificazioni*

Technical info / *Info tecniche*

220..240Vac 50..60Hz | IP20 | RG1 unlimited

Other colour temperatures and CRI available upon request. All values marked with an (*) are rated values. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
Luminous flux is subject to a normal technology drop over time. A.A.G. Stucchi reserves the right to make technical changes without prior notice. Real power: ±10% tolerance

Other colour temperatures and CRI available upon request. All values marked with an (*) are rated values. Unless stated otherwise, the values apply to an ambient temperature of 25°C.
Luminous flux is subject to a normal technology drop over time. A.A.G. Stucchi reserves the right to make technical changes without prior notice. Real power: ±10% tolerance